

轧盖机 CAPPING MACHINE

ALUMINIUM CRIMPING MACHINE SERIES



Description

The state-of-the-art single or multiple blades design along with the most cGMP satisfied material make each crimping in one complete stage.

设备概述

轧盖机通过单个、三个或多个轧盖刀连续对西林瓶进行轧盖。能自动完成进瓶、上盖、轧盖、出瓶等过程。设备设计和用材完全符合cGMP规范。



ZGX10轧盖机 ZGX10 Capping Machine

Features

- Continuous capping by one, three or multi sealing rollers, 2-250ml container sizes applicable
- PLC controlled operation via touch screen, No Vial No Capping combined with safety alarm functions
- Multi container sizes applicable, less and quick changing of sizeparts
- Driving by the qualified continuous variable motor and electronic cam
- Rigid crimping roller, low container breakage and high successful sealing rate
- Crimping dust exhaust device in compliance with cGMP guideline
- Smooth capping edge, less particle generation
- Machine can be operated individually or synchronized with others

技术特点

- 连续式单刀、三刀或多刀形式轧盖，可适应2~250ml瓶子
- PLC程控的全自动设备，触摸屏操作，含倒瓶停机，无瓶止盖等自控功能，安全和报警功能完备
- 多规格生产，规格件更换方便快捷
- 采用高级无级变速电机和高精度电子凸轮，结构紧凑，性能稳定，维修方便
- 瓶子破损率低，轧盖成功率高
- 带有铝尘颗粒吸除装置，符合cGMP规范
- 对不同尺寸规格的铝盖适应性好，轧盖边缘整齐，大大减少落屑和滚皱现象
- 可单机也可联线运行

ZGD12轧盖机 ZGD12 Capping Machine



技术参数 Parameters

设备型号 Model	ZGS01	ZGD8	ZGX10	ZGD12
电源 Power supply		3 phases, 380V/50Hz		
功率 Power	1.2 KW	1.6 KW	1.6 KW	1.6 KW
噪声 Noise	≤70db	≤70db	≤70db	≤70db
最高灌装速度 Output vials/hr	12000	18000	24000	30000
轧盖成功率 Completion rate	99.80%	99.80%	99.80%	99.80%
机器的尺寸 Dimension	1440×850×1800	1500×1050×1800	1860×1200×1800	1860×1200×1800
传送台高度 Feeding height	900±20mm	900±20mm	900±20mm	900±20mm
机器重量 Weight	350kg	650kg	650kg	650kg

ZGS01 轧盖机

ZGS01 CAPPING MACHINE



生产能力(瓶/小时) Capacity (Vials/Hour)

Model	2-5ml	7ml	10ml	15ml	20ml	30ml	50ml	250ml
ZGS01	9000	7200	7200	6300	6300	6000	4200	2700
ZGD8	21000	18000	18000	12000	12000	12000	N/A	N/A
ZGX10	27000	24000	24000	18000	18000	15000	N/A	N/A
ZGD12	33000	30000	30000	24000	24000	18000	N/A	N/A

上海天延制药机械有限公司

Shanghai Tianyan Pharmaceutical Machinery Co., Ltd.

地址 (Add) : 中国上海青浦工业园区漕盈路3590号
No.3590, Caoying Road, Qingpu Industry Zone, Shanghai, China

电话 (Tel) : 86-21-59228825 传真 (Fax) : 86-21-59228830

www.tianyanshanghai.com

